

## LA-UR-21-29077

Approved for public release; distribution is unlimited.

Title: AI Enhanced Discretizations for High-Fidelity Physics Simulations

Author(s): Brady, Peter T.  
Livescu, Daniel  
Sharan, Nek

Intended for: Report

Issued: 2021-09-15

---

**Disclaimer:**

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by Triad National Security, LLC for the National Nuclear Security Administration of U.S. Department of Energy under contract 89233218CNA000001. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.


# AI Enhanced Discretizations for High-Fidelity Physics Simulations

Peter Brady; Daniel Livescu; Nek Sharan  
CCS-2


# Introduction

- Non-dissipative schemes are preferred for high-fidelity turbulent flow and aeroacoustics simulations
- Practical applications need stable boundary closures that ensure stability without adding artificial (numerical) dissipation

Turbulent mixing layer



Acoustic scatter







# Boundary instabilities with non-dissipative schemes

**Time stability.** A method is **time-stable** if for homogenous boundary data and no source terms, there is a unique solution  $\mathbf{u}(t)$  satisfying

$$\|\mathbf{u}\|_{\Delta x} \leq K \|\mathbf{f}\|_{\Delta x}, \quad \text{or} \quad \frac{d}{dt} \|\mathbf{u}\|_{\Delta x}^2 \leq 0,$$

where  $K$  is independent of  $\Delta x$ ,  $\mathbf{f}$  and  $t$ .  $\mathbf{f}$  denotes the initial data.



# Sufficient conditions for time stability

- For a semidiscrete approximation


$$\frac{d\mathbf{v}}{dt} = M\mathbf{v} + \mathbf{b}$$

$$\mathbf{v}(0) = \mathbf{f}(x),$$

$M$  = system matrix       $\mathbf{b}$  = boundary data

- Sufficient conditions for time-stability:
  - All eigenvalues of  $M$  have non-positive real part and the geometric multiplicity of every eigenvalue with zero real part is equal to its algebraic multiplicity
  - There exists a real symmetric positive definite matrix  $H$  such that  $\mathbf{x}^T H M \mathbf{x} \leq 0$  for all  $\mathbf{x} \Rightarrow M^T H + H M$  is negative semidefinite


# Derivation of time-stable boundary stencils for centered schemes




# Derivation of time-stable boundary stencils for centered schemes

## Cost Function


$$J = \text{loss}(\Lambda_{\mathcal{L}}^+, \sigma_{\mathcal{L}} \mathbf{I}_{\mathcal{L}}^+) + \text{loss}(\Lambda_H^-, \sigma_H \mathbf{I}_H^-) = \sum_{i=0}^{n-1} \left( \Lambda_{\mathcal{L},i}^+ - \sigma_{\mathcal{L}} I_{\mathcal{L},i}^+ \right)^2 + \sum_{i=0}^{n-1} \left( \Lambda_{H,i}^- - \sigma_H I_{H,i}^- \right)^2$$





# Controllable generation in image synthesis




# Controllable generation in image synthesis



# Controllable generation in image synthesis



# Controllable generation in image synthesis




Original




Age



Eyeglasses



Gender




Pose





# Controllable generation of boundary stencils

- Step 1: Coarse-grained search ➡ Fix the weights and biases
- Step 2: Finer modifications to the noise vector for time stability



# Numerical results: Scalar hyperbolic problem

## Eigenvalue spectrum from the derived schemes



## Convergence rate

$n$	2 - 4 - 2 scheme				3 - 6 - 3 scheme			
	$\log_{10} \ \varepsilon\ _2$	Rate	$\log_{10} \ \varepsilon\ _\infty$	Rate	$\log_{10} \ \varepsilon\ _2$	Rate	$\log_{10} \ \varepsilon\ _\infty$	Rate
20	-1.973422		-1.703554		-2.279161		-1.948476	
40	-2.916809	3.134	-2.574815	2.894	-3.449783	3.889	-3.196234	4.145
80	-3.835924	3.053	-3.486709	3.029	-4.631867	3.927	-4.366281	3.887
160	-4.745814	3.023	-4.384746	2.983	-5.826623	3.969	-5.557024	3.956
320	-5.651926	3.010	-5.282615	2.983	-7.026841	3.987	-6.756342	3.984
640	-6.556365	3.004	-6.197129	3.038	-8.229245	3.994	-7.958516	3.994



# Numerical results: Inviscid Burgers' equation

$$\frac{\partial U}{\partial t} + \frac{\partial}{\partial x} \left( \frac{U^2}{2} \right) = f_U. \quad 0 \leq x \leq 1, \quad t \geq 0,$$


$$U(x, t) = \sin 2\pi(x - t) + C,$$

$$f_U(x, t) = \pi \sin 4\pi(x - t).$$

## Stability



# AI Enhanced Discretizations for High-Fidelity Physics Simulations



Time stable simulation of varying coefficient scalar hyperbolic equation

## ***Project Description:***

***Combine theoretical analysis with deep learning to design efficient numerical discretizations for direct numerical simulations of fluid flow.***

## ***Project Outcomes:***

***Developed a controllable generation approach using deep NN to derive time-stable, high-order numerical schemes for high-fidelity physics simulations.***

***PI: Peter Brady***

***Total Project Budget: 60k***

***ISTI Focus Area: Data Science and AI Infrastructure / Simulation***

END